

Specification

Outdoor Camera	
Camera Resolution	700TVL
Night Vision Distance	More than 2 meters
Working Temperature	-35 degrees ~ +55 degrees
Intensity of Illumination	3m-6m night vision
Lens	2.3mm
Dimension	180mm(L) x 98mm(W) x 45mm(H)
Installation	Surface mounted
Material	Metal panel , ABS rainproof
Net Weight	400g
Model	IDS
Indoor Monitor	
Screen	7" LCD Digital 16:9 Display
Effective Pixels	800 x 480
Delay Calling Time	120s ± 10%
Delay monitoring time	40s ± 10%
Adapter Input	AC100 - 240V 50-60HZ
Adapter Output	DC15V
Unit Consumption	Less than 6W, standby less than 0.5W
Working Temperature	-35 degrees ~ 55degrees
Installation	Wall mounted
Dimension	240mm(L) x 150mm(W) x 23mm(H)
Weight	500g
Model	V70C

This Hard-wired Video Door phone Intercom System consists of two 7" color TFT monitor and one door camera. Upgraded chips are adopted for highly stable performance and it has a nice appearance. It is your perfect choice to use in villas with 700 lines CMOS camera, which can achieve monitoring, dual-way intercom and unlocking. You also can monitor outside image even without people pressing the Monitor button on the Indoor unit.

This new released outdoor unit has a code keypad, it supports to unlock via password or RFID card, very convenient to unlock. Besides, it is fully waterproof, supports outdoor working, with 6 LED for night vision.

Features

- With micro-processing technology, auto-remote control, excellent performance and high reliability.
- The TFT 7 inch digital color LCD for monitor.
- Clear night-viewing , 24 hours monitoring, calling, speaking and unlocking remote controlling etc.
- Additional monitor available up to 6(optional) and 3 outdoor cameras at most.
- TFT color screen with low power consumption, no radiation and high definition.
- Hands-free intercommunication.
- Brightness, chroma and volume adjustable.
- Comes with 10 RFID keyfobs, a push release button switch.
- Support maximum 500 id keyfobs or cards.
- Supports one password, you can unlock via code or RFID card
- Fully waterproof, support outdoor working.
- 25-chord melody rings for option.
- Cabling: 4-core connection cable
- 700 TVL CMOS Camera.
- Supports communication between two monitors.
- Do not disturb mode